

TIGER



LOW & MEDIUM DUTY AIRLESS SPRAY PAINTING EQUIPMENT

The range is suitable for liquids like wood finish, varnishes, stains & all types wood coatings

FEATURES

- Pneumatically sensed Stall free Air Motor
- Small actuating stroke
- Stainless Steel rust proof Hydraulic Body
- Easy to carry & maintain
- Ice free Air Motors
- Lower air consumption
- Compliance to EU Norms
- Easy to change color with almost no wastage



h II B T6 Gb

ACCESSORIES



TECHNICAL SPECIFICATIONS

Type	15:16	15:30	25:16
Ratio*	15:1	15:1	25:1
Output per Cycle theoretical	16 cc	30 cc	16 cc
Air Motor Piston Ø	60 mm	80 mm	80 mm
Stroke Length	50 mm	50 mm	50 mm
Recommended Spray Volume @ 25 cycles/min	0.4 ltr.	0.75 ltr.	0.4 ltr.
Air Inlet Pressure Max.	6 bar	6 bar	6 bar
Output Pressure Max.	96 bar	90 bar	150 bar
Air Consumption scfm @ 25 cycles/min	1.75	3	3

*Other ratios and flow on request



V R COATINGS PVT. LTD.

J -138, MIDC Bhosari, Pune - 411 026. INDIA.

Tel.: +91 (020) 8237086924 / 27130331 Fax : +91 (020) 27130891

E-mail.: sales@vrcoatings.com Web : www.vrcoatings.com